

CHANGES TO SUPPLY TENDER DOSSIER No.2

Contract Title: Supply of Equipment for Mersin ITS SAP

Publication Ref: EC-ENEST/ANK/2026/EA-OP/0040

The following amendments and/or corrections are made to the Supply Tender Dossier.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - LOT 2 – Traffic Management System Equipment, 3. Installation and Commissioning Requirements, Page 8 of 15

Delete the text:

Installation and integration of Mobile NVR units with existing surveillance camera systems in vehicles.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.1.8

Delete the text:

The sensor's working temperature shall cover the range of -20°C to +55°C.

And replace with:

The sensor's working temperature shall cover the range of -40°C to +80°C.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.1.16

Delete the text:

The sensor shall be at least 1 / 2.4 " 2M pixel CMOS type.

And replace with:

The sensor shall be between 1 / 2.8" and 1 / 2.4" (inclusive), and at least 2M pixel CMOS type.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.1.17

Delete the text:

The sensor shall have at least M12- 2.2 mm lens, maximum M12 2.7 mm lens.(shall be between 2.2 mm to 2.7 mm) The FOV shall be at least 120° and VFOV shall be at least 62,5°.

And replace with:

The sensor shall have minimum M12- 2.2 mm lens, maximum M12 2.8 mm lens. The FOV shall be at least 120° and VFOV shall be at least 62,5°.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.1.22

Delete the text:

The sensor shall comply with following standards as minimum: EN50155 - IEC60068-2-7EH – IP66 – EN50102 – ROHS – FCC – EMC – CE standards.

And replace with:

The sensor shall comply with following standards: IP65 or higher ingress protection; IK08 impact protection in accordance with EN62262 or equivalent; compliance with ISO 16750-3; and CE marking with an EU Declaration of Conformity covering applicable EU product legislation, including EMC and RoHS requirements where applicable.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.1.24

Delete the text:

All equipment supplied shall be fully compliant with the requirements mentioned in the "directive on the modification of the directive for manufacturing, modification and assembly of vehicles" published in the Official Gazette No. 32817, dated 18.02.2025.

Add revised text to:

Part B - Annex II+III Technical Specifications + Technical Offer, LOT 2 – Traffic Management System Equipment, 1. General requirements (Page 8 of 15)

1.5. All equipment supplied under this contract shall be fully compliant with the requirements mentioned in the "Regulation on the Manufacture, Modification and Assembly of Vehicles" published in the Official Gazette No. 29869, dated 26.10.2016, including all subsequent amendments.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.2.2

Delete the text:

MNVR video output shall support 1 ch HDMI, 1 ch CVBS and 1 ch VGA.

And replace with:

MNVR video output shall support at least 1 ch HDMI or 1 ch CVBS or 1 ch VGA.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.2.4

Delete the text:

MNVR shall support 3G or 4G network and optional to support WIFI.

And replace with:

MNVR shall support 4G/LTE network.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.2.5

Delete the text:

The MNVR shall support 1 × M.2 SSD and shall be supplied with a minimum of one 1 TB M.2 SSD.

And replace with:

The MNVR shall be supplied with a minimum of one 1 TB industrial grade 2.5 inch SSD or one 1 TB M.2 SSD.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.2.7

Delete the text:

MNVR's operating temperature shall cover the range of -30°C to +55°C, and operating humidity shall be between 10% to 90% or larger.

And replace with:

MNVR's operating temperature shall cover the range of -30°C to +70°C, and operating humidity shall be between 10% to 90% or larger.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.2.9

Delete the text:

MNVR shall have a built-in GPS module for accurate location tracking

And replace with:

MNVR shall have a built-in/integrated or externally connected GPS module for accurate location tracking.

Part B - Annex II+III Technical Specifications + Technical Offer, Lot 2 - Specification 2.2.11

Delete the text:

The MNVR device shall have EN 50155, E-Mark, and ISO 16750-3 certifications.

And replace with:

The MNVR device shall have E-Mark, and ISO 16750-3 certifications.
